

Circular Manway Cover With PED

Item TS-C01 (ø308 - ø708 mm external frame)



- PED approved manway cover for pressure applications in the foodindustry e.g.
- Manufactured in Europe.
- Pharma modification is possible.
- Can be used in full vacuum applications.
- In stock in AISI316L (EN 1.4404).
- Silicone gasket type TS-C01.G.XXX.X
- Other gaskets in **NBR/VITON/EPDM**
- Gasket not glued on lid.
- Handwheel in AISI304 (EN 1.4301).
- Integrated sight glass is possible.

Item no. (All in mat. EN 1.4404)	Df (mm)	Hf (mm)	Tf (mm)	H	Temperatur Max. (C°)				
					50 C°	100 C°	150 C°	200 C°	250 C°
					Pressure Max. (bar)				
TS-C01.308.150.04.S *	Ø 308	150	4	4	4,5	4,0	4,0	3,5	3,5
TS-C01.308.150.06.S	Ø 308	150	4	6	8,5	8,0	7,5	7,0	7,0
TS-C01.310.150.08.S	Ø 310	150	5	8	10,5	9,5	9,0	8,5	8,5
TS-C01.408.150.04.S	Ø 408	150	4	4	2,0	1,5	1,5	1,5	1,5
TS-C01.408.150.06.S	Ø 408	150	4	6	4,5	4,0	4,0	3,5	3,5
TS-C01.408.150.08.S	Ø 408	150	4	8	6,5	6,0	6,0	5,5	5,5
TS-C01.408.150.10.S *	Ø 408	150	4	10	8,5	7,5	7,5	7,0	7,0
TS-C01.410.150.12.S *	Ø 410	150	5	12	10,0	9,0	8,5	8,0	8,0
TS-C01.458.150.04.S	Ø 458	150	4	4	1,5	1,0	1,0	1,0	1,0
TS-C01.458.150.06.S	Ø 458	150	4	6	3,0	3,0	3,0	2,5	2,5
TS-C01.458.150.08.S	Ø 458	150	4	8	5,5	5,0	4,5	4,5	4,5
TS-C01.458.150.10.S	Ø 458	150	4	10	6,5	6,0	6,0	5,5	5,5
TS-C01.458.150.12.S *	Ø 458	150	4	12	8,0	7,5	7,0	6,5	6,5
TS-C01.508.150.04.S	Ø 508	150	4	4	1,0	1,0	1,0	1,0	1,0
TS-C01.508.150.06.S	Ø 508	150	4	6	2,5	2,0	2,0	2,0	2,0
TS-C01.508.150.08.S	Ø 508	150	4	8	4,0	4,0	3,5	3,5	3,5
TS-C01.508.150.10.S	Ø 508	150	4	10	5,5	5,0	4,5	4,5	4,5
TS-C01.508.150.12.S	Ø 508	150	4	12	6,5	6,0	5,5	5,5	5,5
TS-C01.508.150.14.S *	Ø 508	150	4	14	7,5	7,0	6,5	6,0	6,0
TS-C01.608.150.06.S	Ø 608	150	4	6	1,5	1,0	1,0	1,0	1,5
TS-C01.608.150.08.S	Ø 608	150	4	8	2,5	2,5	2,0	2,0	2,0
TS-C01.608.150.10.S *	Ø 608	150	4	10	4,0	3,5	3,5	3,0	3,0
TS-C01.608.150.12.S *	Ø 608	150	4	12	4,5	4,0	4,0	4,0	3,5
TS-C01.608.150.14.S	Ø 608	150	4	14	5,5	5,0	4,5	4,5	4,5
TS-C01.708.150.06.S *	Ø 708	150	4	6	1,0	1,0	1,0	0,5	0,5
TS-C01.708.150.08.S *	Ø 708	150	4	8	1,5	1,5	1,5	1,5	1,5
TS-C01.708.150.10.S *	Ø 708	150	4	10	2,5	2,5	2,0	2,0	2,0
TS-C01.708.150.12.S *	Ø 708	150	4	12	3,5	3,0	3,0	3,0	3,0
TS-C01.708.150.14.S *	Ø 708	150	4	14	4,0	3,5	3,5	3,5	3,5

* Not in stock, deliverytime app. 4 uger.

Item no. breakdown

Eks. TS-C01.308.150.08.S

-**TS**- = Tec Scandinavia

-TS-**C01** = Type no. (C = Circular)

-TS-C01.**308**. = Ext. diameter (mm)

-TS-C01.308.**150**. = Frame height (mm)

-TS-C01.308.150.**08**. = Handwheels

-TS-C01.308.150.08.**S** = Silicone gasket

Sketch

