



Degree of accuracy (from T0)	0.5 - 3	3 - 6	6 - 30	30 - 120	120 - 400	400 - 1000	1000 - 2000	2000 - 4000	<div><div></div><div>13/</div></div>	
Coarse (C)	N/A	N/A	N/A	N/A	N/A	±2	±3	±4	<div><div></div><div>23/</div></div>	
Medium (M)	±0.1	±0.1	±0.2	±0.3	±0.5	N/A	N/A	N/A	<div><div></div><div>14/</div></div>	
GENERAL TOLERANCES FOR WORKING DIMENSIONS (UNI 2789/1 Ex 5307 DIN 7189)									<div><div></div><div>26/</div></div>	<div><div></div><div>28/</div></div>

Surface Roughness Tolerance

Description: Manway for -1 to 2,3 bar pressure, -20° to 150°

TEC

Italy - Scandinvia

Address: TEC Scandinvia AGS

DK - 8840 Sundens SV

Phone: +45 86 43 39 97

Email: info@tec-scandinavia.dk

Comes with PED

Art. no.:

TS-C01.508.150.04

Available Steel Grade:

EN 1.4404 (316L) / EN 1.4301 (304L)

Available gasket materials:

EPDM / VITON / Silicone / NBR

REVISION

1.0

Format A2