


Degree of accuracy (from -10)	0.5 - 3	3 - 6	6 - 30	30 - 120	120 - 400	400 - 1000	1000 - 2000	2000 - 4000	$\nabla^{12.5}$	$\nabla^{2.5}$	$\nabla^{1.6}$	$\nabla^{0.8}$	$\nabla^{0.4}$	$\nabla^{0.2}$	$\nabla^{0.1}$
Coarse (C)	N/A	N/A	N/A	N/A	N/A	± 2	± 3	± 4							
Medium (M)	± 0.1	± 0.1	± 0.2	± 0.3	± 0.5	N/A	N/A	N/A							

GENERAL TOLERANCES FOR WORKING DIMENSIONS (UNI 2780/1 EX 5307 DIN 7180)

Surface Roughness Tolerance	$\nabla^{12.5}$	$\nabla^{2.5}$	$\nabla^{1.6}$	$\nabla^{0.8}$	$\nabla^{0.4}$	$\nabla^{0.2}$	$\nabla^{0.1}$
-----------------------------	-----------------	----------------	----------------	----------------	----------------	----------------	----------------

Description: Manway for -1 to 3,2 bar pressure, -20° to 150°




Address: TEC Scandinavia AS
DK - 8840 Rindøvej 5V
Phone: +45 86 43 39 97
Mail: info@tec-scandinavia.dk

Art. no.: TS-C01.608.150.08

Available Steel Grade:
EN 1.4404 (316L) / EN 1.4301 (304L)

Available gasket materials:
EPDM / VITON /
Silicone / NBR

Revision: 1.0



Comes with PED